

800x1600_{mm}

MIGHTY SIZE





Architecture

Accord is a leading ceramic manufacturing company since its origin in the year 2007 and has been dominating the industry with its innovative products. Accord has created a rich legacy for the brand with an unconventional range of products that have distinctive designs and surfaces in vivid sizes. At Accord we endeavour for creating epic products.

Manufacturing the excellent quality has been our prime concern since our existence. With a large-scale factory area and a team of cooperative professionals, Accord has its own competitive superiority to endure in the contemporary domain of slab tiles. For keeping up with the trends, Accord's R&D team have been researching the market regularly. Our R&D team is full of keen analytics and researchers who keep a constant eye over the market statistics to align ourselves with the daily trends.



FINISHES



















www.accordceramics.com



After years of research and keen analysis, Accord has cracked the code to create a unique range of finishes. This watchful eye on the evolution of vogue trends allows us to create materials that are highly unique and advanced.

EATURES

























15 YEARS TO

Build, Create,

INNOVATE & MAINTAIN TRUST



"Knowledge is worthless if it is not having the direction of customer satisfaction by offering value for money".

Keeping this philosophy in our mind & zeal to serve the society in our heart, production becomes creation at Accord group of companies. The same is reflected in our end products which are certified with ISO 9001:2015 & CE marking, "Assist people achieve their objectives & in return you will achieve yours". We believe that our success lines in the success of our business partners. We put every effort to help our business associates to achieve the highest level of satisfaction & monetary benefits by quality products, competitive price & above all, a clean policy. Accord management is keeping an eagle's eye on the changing vogues to meet & beat every challenge be it quality, design or price.



Building Area

115k
sq. mtrs

Land Area
150k
sq. mtrs

Office Area **7**K

sa. mtrs

Production Capacity

13m

sa, mtrs per vear

EXPERIENCE NEW QUALITY &

Technology



TEST

State-of-the-art laboratories which continually test material properties and functional performance.

MONITORING

From the choice of raw materials to their storage, grinding of the mixture, shaping and firing of the tiles; from manufacturing process to quality control

AUTOMATION

System automation which performs size and flatness control with lazer and IR technology.

DESIGN

In house international standard design enterprise.

MANAGEMENT

Integrated electronic management information systems which monitor and relay quality and production information in real time.

Our Technology





















800 X 1600 mm

MIGHTYSIZE

These are the most conventional tile as it is easy to lay, and extremely versatile; which is suitable for rooms of any size with many different technical and aesthetic requirements.













































HIGH GLOSSY FINISH 9mm thickness







ROMANTIC STATUARIO












FLOOR: ROMANTIC STATUARIO



























GOLD AGATE ONYX





BLUE AGATE ONYX






BIANCO LASA









ARISTONE CEROBE



































FLOOR & WALL : PATAGONIA









































PIETRA SEPIA

BOTTICINO CLASSIC



WALL : ALDO BEIGE | FLOOR : ALDO BEIGE





























BRECCIA AURORA BIANCO























































































DOMINO MARFIL
























ARMANI GOLD




























PERSIAN BLUE




































MARINA PEDRA 3 RANDOM





















































STOINIS NATURAL
















*Dark High Glossy Series Ready To Load






























FLOOR: TITANIUM BROWN





HIGH GLOSSY FINISH 9mm thickness


















WALL: PORT LORENT FLOOR: STATUARIO BRONZE


New PORT LORENT *Dark High Glossy Series



New STATUARIO SILVIA



HIGH GLOSSY FINISH 9mm thickness


















New ARGOS BLACK 4 FACE CONTINUE



WALL: EMBER WHITE















New GLOBAL BEIGE 4 FACE CONTINUE

ENDMATCH





New OLIVA LATTE 3 FACE CONTINUE

ENDMATCH





New | ONYX ALPINE 4 FACE CONTINUE













ENDMATCH



New MARBELLA WHITE

ENDMATCH





ENDMATCH




New PIETRA SMOKE 3 FACE CONTINUE










































WALL: NORWAY GREY & NORWAY SEAL | FLOOR: NORWAY SEAL





































WALL: LOVA NERO





















STONEAGE COPPER

























BURBERRY GREY

























WALL : STUCCO BEIGE | FLOOR : STUCCO BEIGE














New ARIZONA LATTE



New MOSAIK TAUPE




















WALL: MOSAIK WHITE FLOOR: MOSAIK TAUPE



















ALPI GREY






CIPRIA MATTONE A+B Book Match



FLOOR: ALPI GREY

















TATUARIO MAXI 3 RANDO





IBECCIO BLUE A+B Book Matc



FLOOR & WALL : STATUARIO MAXI

TECHNICAL SPECIFICATION OF ACCORD SLAB VITRIFIED TILE

TEST DISCRIPTION						
CHARACTERISTIC	TEST METHOD	STANDARD AS PER ISO-13006/EN14411 GROUP	ACCORD VALUE			
Deviation in Length	IS-13630-1	±0.50%	±0.10%			
Deviation in Width	IS-13630-1	±0.50%	±0.10%			
Deviation in Thickness	IS-13630-1	±5.00%	±5.00%			
Straightness of Sides	IS-13630-1	±0.50%	±0.10%			
Rectangularity	IS-13630-1	±0.60%	±0.15%			
Surface Flatness	IS-13630-1	±0.50%	±0.20%			
Surface Quality	IS-13630-1	Min. 95%	Min. 95%			

PHYSICAL PROPERTIES							
Water Absorption	IS-13630-2	≤0.50%	≤0.50%				
Modulus of Rapture(N/mm2)	IS-13630-6	Min. 35N/mm²	Min. 37N/mm²				
Breaking Strength(N)	IS-13630-6	<7.5mm-700N ≥7.5mm-1300N	≤7.5mm-1000N ≥7.5mm-1400N				
Moisture Expansion(mm/m)	IS-13630-3	0.06 Max	0.01 Max				
Scratch Hardness of Surface	IS-13630-13	Min. 4	Min. 4				
Resistance of Surface Abrasion(Glazed Tiles)	IS-13630-11	As per Mfg.	Class II Min.				
Co-Efficent of Linear Thermal Expansion	IS-13630-4	As per Mfg.	6.5x10 ^{-0.6} Max.				
Thermal Shock Resistance	IS-13630-5	10 Cycles Min.	10 Cycles Min.				
Crazing Resistance	IS-13630-9	As per Mfg.	5 Cycles at 7.5Bar Pressure				
Impact Resistance-Coefficent of Restitution	IS-13630-14	As per Mfg.	0.55 Min				
Frost Resistance	IS-13630-10	As per Mfg.	No Damage				
Bulk Density (g/cc)	IS-13630-2	>2.0 gm/cc	>2.0 gm/cc				

CHEMICAL PROPERTIES						
Resistance of Staining	IS-13630-8	Class I Min.	Class I			
Resistance of Household Chemicals	IS-13630-8	Class AA Min.	Class AA			
Resistance to Acids & Alkalis	IS-13630-8	As per Mfg.	Min. Class A			
Slip Resistance	150-13006/EN1444 Group B A	As per Mfg.	As per Mfg.			

PACKING DETAIL

No.	Size	Inickness (approx.)	Pieces/Box	Area/Box	WT./BOX (approx.)
01	800x1600mm	9mm	2 pcs.	2.56 sq. mtr.	53 kg

ARK SLAB LAYING INSTRUCTIONS


- Plaster the surface of the floor to be tiled smooth and complete the plastering and curing at least two hour prior to tilling.
- Before fixing **ARK SLAB**, lay them out in desired pattern and make sure that give acceptable blend of colour. Please not that certain amount of shade variation is inherent in the manufacture of a fully vitrified ceramic tile.

 THE COMPANY WALL BEAR NO LIABILITY AFTER THE TILES ARE FIXED.
- For fixing **ARK SLAB**, we recommend the use of the tile fixing adhesive for best result. Also follow the tile fixing instructions provided along with adhesives.
- For fixing **ARK SLAB** on the floor using sand and cement follow the instructions given bellow:
- Use cement and sand mortar in the ratio of 1:4 add some water to create a consistent paste.
- Once the mixing has been completed do not add any further water to create a consistent paste.
- Apply a 20-30mm layer of bedding material over an area of 1 square meter at a time on the surface of the area, Apply a fine slurry to the back of the tile to ensure proper and dull bedding, press gently for even adherence at the back of the tile.


 DO NOT USE IRON HAMMER OR SOME HEAVY MATERIAL TO PRESS THE TILES.
- ☐ For fixing **ARK SLAB** on dado, we recommend the use of adhesive. Please follow the manufacture's instructions for the same. We do not recommend the use of sand and cement for fixing on dado.
- Mark and layout the tiles from the center of the area to be tile so that cut tiles. If any will be on the outer edges to words the walls.
- The work size which we try to maintain for better technical performance is 1200x2400mm, 800x2400mm, 900x1800mm, 800x1600mm, & 1200x1200mm on average. It is advisable to maintain a gap of 1mm to 3mm between every two tile to allow for possible expansion as
 - per BIS/EN tolerance norms. This would give the coverage area as mentioned in the cartoon.
- ☐ Complete the tile laying process by pressing the center of the **ARK SLAB** firmly into place along the walls/floors.
- Allow 3-4 days for bed curing. After this period fill the joints with grouts.
- Fifteen minutes after finishing the grouting process, wipe off excess grout with a damp sponge and polish the tile with a soft and dry cloth for a clean surface. The tile can also be cleaned by mild acid(however hydrofluoric acid and its derivatives should not be used)
- Please note that the company does not accept any liability in case of problems arising out of non-adherence to these fixing instructions.

TILING POSSIBILITIES

800x1600mm



1200x1200mm









ACCORD VITRIFIED PVT. LTD.

S. No. 151/P3, Near Narmada Canal, Morbi - Halvad Road, At. Unchi Mandal, Morbi - 363 642, Gujarat, INDIA

Contact: +91 97264 20209

Email: info@accordvitrified.com | Web.: www.accordceramics.com

Join us on: f in

